

"THE AUGER IS THE ANSWER"



<u>SANI-TECH AUGER</u> COMPACTORS DO IT ALL

Auger-Type compactors **pre-crush** and compact in one powerful motion. While processing material, augers run **continuously** in a forward direction, crushing and reducing the size of virtually everything they're fed. This allows them to compact material **faster** and achieve **higher compaction ratios** than any other compaction system on the market today.

MODEL ST2054/40

The Sani-Tech Model ST2054/40 20HP heavy-duty auger compactor is ideal for the types of waste and recyclables generated by:

- Cardboard Recyclers Distribution Centers Industrial Parks
 Municipalities Manufacturers
 - Pallet Recyclers Thrift Stores Wood Recyclers

With Sani-Tech auger compactors, all you have to do is throw material into the compactor, turn it on and walk away. When you return, the material will be safely compacted into a receiver bin and the compactor will be ready for more.

COST SAVINGS IS THE BOTTOM LINE

Substantial reductions in operating costs are obtained by: increased compaction, labor savings and reduced trash pick-ups.

STATIONARY COMPACTOR MODEL ST2054/40

Roll-Off:

10 Cubic Yard CCS

25 Cubic Yard CCL

30 Cubic Yard CCL

15 Cubic Yard CCS 14' 10"

20 Cubic Yard CCS 18' 10"

35 Cubic Yard CCL* 18' 10"

40 Cubic Yard CCL* 20' 10"

47 Cubic Yard CCL* 22' 8"

15 Cubic Yard

20 Cubic Yard

25 Cubic Yard

30 Cubic Yard

35 Cubic Yard*

40 Cubic Yard*

SPECIFICATIONS

Motor: 20 HP

Auger Diameter: Tapered 54" to 40"

Auger Speed: 6 RPM

Displacement Rate: 350 Cu. Yds./Hr. Cycle Time: Fully Adjustable

Electrical: 240V / 480V - 3 Phase Amperage: 60 Amp / 30 Amp Drive: Electro-Mechanical Auger Torque: 500,000 In. Lbs.

Control Panel: UL Listed

- Keylock Start/Reverse & Emergency Stop

Compactor Weight: 10,000 Lbs.

Auger Penetration: 9 to 15 inches into bin

Clear Top Opening: 90" x 72"

Hopper Capacity*: ____ Cubic Yards
Swing Door Size*: 42" W X 36" H

*Hopper specifications for HOP-02 (not shown)

**Consult Factory for Additional Hopper Options

RECEIVER BINS

Length

9'10"

9' 10"

12' 10"

15' 10"

13' 10"

18' 10"

16' 10"

20' 10"

22' 10"

Receiver Body

Tare Wgt.

3,500 lbs.

4.100 lbs.

4,100 lbs

5,000 lbs.

5.000 lbs.

5,800 lbs.

5,800 lbs.

6.600 lbs.

6,600 lbs.

7,100 lbs.

7.100 lbs.

7,700 lbs.

7,700 lbs.

7,800 lbs.

Overall

Length

18'

18'

23'

21'

27'

24'

22'

27

25'

29'


27'

31'

29'

30' 10"

Note: Specifications are subject to change without notice to accommodate design improvements.



Standard Features:

- ♦ Abrasion Resistant Alloy Steel Auger
- Replaceable Cast Auger End Wear Plate
- High Performance Roller Bearings
- ♦ Full Gasket on Auger Nozzle
- ♦ Adjustable Compaction Density
- ♦ Bin Full Indicator
- High Quality Machinery Enamel Finish
- Liquid Tight Auger Chamber
- Safety Interlock System
- ♦ Meets ANSI & OSHA Standards

Optional Features:

- Electric Greaser System*Recommended for ALL Systems
- Odor Control Systems
- ♦ Electric Cart Dumper
- Custom Paint Colors
- Liquid Drain System
- ♦ Photo Eye Automatic Start
- Remote Pendant Control Station
- Bin Near Full Sensor

- ♦ Bin Gone Sensor
- Thru-the Wall Chute
- Dock Door Enclosure
- Custom Hood Designs
- **♦** Compaction Bins
- ♦ Bin Hole Diaphragm
- ♦ Fire Ports on Bin
- Custom Engineering

*Consult factory for custom design work.



Sani-Tech Systems Inc. PO Box 444, Duvall, WA 98019 (425) 788-6444, Fax: (425) 844-8625 **E-mail:** compactorinfo@sanitech.net **Web:** www.sanitech.net

^{*}Request prior confirmation with refuse hauler for length of this unit.

** Consult Factory for Additional Bin Sizes