


SANI-TECH



Auger Style Refuse and Recycling Compactors



SANI-TECH AUGER COMPACTORS DO IT ALL

Auger-Type compactors **pre-crush** and compact in one powerful motion. While processing material, augers run **continuously** in a forward direction, crushing and reducing the size of virtually every-thing they're fed. This allows them to compact material **faster** and achieve **higher compaction ratios** than any other compaction system on the market today.

MODEL SC540/24

Sani-Tech Model **SC540 5HP** Self-Contained compactors are ideal for wet, hazardous or messy waste and where cleanliness and sanitation are the highest priority. They outperform the competition because they:

- Are 100% sealed to prevent liquid and trash spillage during daily operation and emptying.
- Are designed and engineered for high performance and dependable service.
- Uses tapered 40" - 24" auger designed to pre-crush large and bulky trash.
- Allow operators to simply throw material into the hopper, start the compactor and walk away. No wait time, no human intervention.
- Utilize all electric drive systems that run clean and quiet.
- Obtain compaction ratios that are two to three times greater than standard hydraulic compactors to better maximize savings.
- Have inherently small footprints so they can be installed in tight spaces.
- Have a wide variety of optional features to choose from.

COST SAVINGS IS THE BOTTOM LINE

Substantial reductions in operating costs are obtained by: increased compaction, reduced hauls and labor savings.

SELF-CONTAINED COMPACTOR MODEL SC540/24

SPECIFICATIONS

| | |
|--------------------|---------------------|
| Hopper Capacity: | 4.5 Cubic Yards |
| Bi-fold Door Size: | 36" W X 30" H |
| Auger Diameter: | Tapered 40" to 24" |
| Auger RPM: | 8 |
| Motor: | 5 HP |
| Displacement Rate: | 270 cu. yds./hr. |
| Electrical: | 240v/480v - 3 phase |
| Amperage: | 30a / 15a |
| Drive: | Electro-mechanical |
| Control Panel: | UL listed 110 volt |
| Compactor Weight: | 4100 Lbs. |
| Auger Torque: | 204,000 In. Lbs. |

RECEIVER BINS


| Model/ Cu. Yd. | Overall Length | Tare Weight |
|----------------|----------------|-------------|
| SC540/30-15 | 15' - 0" | 6,600 lbs. |
| SC540/30-20 | 18' - 0" | 7,200 lbs. |
| SC540/30-25 | 21' - 0" | 7,900 lbs. |
| SC540/30-30* | 24' - 0" | 8,400 lbs. |
| SC540/30-35* | 26' - 0" | 9,000 lbs. |

For special orders consult factory.

* Note: Universal Cable Systems add an additional 18" to Overall Length.

* Request prior confirmation with refuse hauler regarding length of this unit.

Note: Specifications are subject to change without notice to accommodate design improvements.



*See Bin Brochure for Additional Receiver Information

Standard Features:

- ◆ Abrasion Resistant Alloy Steel Auger
- ◆ Replaceable Cast Auger End Wear Plate
- ◆ Adjustable Running Time
- ◆ Mushroom Stop Switch
- ◆ Adjustable Compaction Density
- ◆ Bin Near Full Indicator
- ◆ High Quality Machinery Enamel Finish
- ◆ Liquid Tight Auger Chamber
- ◆ Safety Interlock System
- ◆ Keylock Start/Reverse Switch
- ◆ High Performance Roller Bearing System

Optional Features:

- ◆ Electric Greaser System
*Recommended for ALL Systems
- ◆ Odor Control Systems
- ◆ Electric Cart Dumper
- ◆ Custom Paint Colors
- ◆ Liquid Drain System
- ◆ Photo Eye Automatic Start
- ◆ Remote Pendant Control Station
- ◆ Bin Gone Sensor
- ◆ Thru-the Wall Chute
- ◆ Dock Door Enclosure
- ◆ Custom Hood Designs
- ◆ Compaction Bins
- ◆ Bin Hole Diaphragm
- ◆ Fire Ports on Bin
- ◆ Custom Engineering

*Consult factory for custom design work.

5hp to 40hp models available for additional applications.

SANI-TECH



Auger Style Refuse and Recycling Compactors